

**磁気平衡式／電流出力型
Servo system Current-output type**

S25P SERIES



RoHS指令
適合品

仕様 SPECIFICATIONS

Ta=25°C, Vcc=±15V

項目 Spec	カタログ品番 Types	S25P050D15X	S25P100D15Y	S25P100D15X	S25P150D15Y
定格電流 Primary nominal current	If	50A	100A	100A	150A
測定抵抗 If=±Aoc at Ta=85°C Measuring resistance If=±Aoc at Ta=85°C	R _L	at ±12V 60Ω~95Ω at ±15V 135Ω~155Ω	at ±12V 0Ω~42Ω at ±15V 20Ω~102Ω	at ±12V 10Ω~65Ω at ±15V 40Ω~95Ω	at ±12V 0Ω~15Ω at ±15V 0Ω~55Ω
定格出力電流 Rated output current	I _O	50mA (巻線比 Turn ratio 1:1000)	50mA (巻線比 Turn ratio 1:2000)	100mA (巻線比 Turn ratio 1:1000)	75mA (巻線比 Turn ratio 1:2000)
出力電流精度 Output current accuracy	X _G	Io±0.5% (Ioは除く without Io)			
オフセット電流※1 Offset current	I _{of}	≤ ±0.2mA (at If=0A)	≤ ±0.1mA (at If=0A)	≤ ±0.2mA (at If=0A)	≤ ±0.2mA (at If=0A)
最大電流 Vcc=±15V, Ta=85°C Maximum current	I _{fmax}	±55A (at R _L =135Ω) ^{※2}	±150A (at 20Ω≤R _L ≤25Ω)	±160A (at 40Ω≤R _L ≤50Ω)	±200A (at 0Ω≤R _L ≤40Ω)
出力直線性 Output linearity	E _L	≤ ±0.15% (at If)			≤ ±0.25% (at If)
電源電圧 Power supply voltage	V _{cc}	±15V (±11.4V~±16V) (Rated Current is restricted by V _{cc})			
消費電流 Consumption current	I _{cc}	≤ ±16mA (Output Current is not included)			
di/dt 応答速度(@90% of If) Response time	tr	≤ 1μS (at di/dt=If/μs)			
出力電流温度係数 Thermal drift of gain	T _{Clo}	≤ ±0.01%/°C (Without Tc I _{of})			
オフセット電流温度係数 Thermal drift of offset	T _{Clof}	≤ ±0.5mA max			
ヒステリシス誤差 Hysteresis error	I _{oh}	≤ 0.3mA (at If=0A → If → If=0A)			
絶縁耐圧 Insulation voltage	V _d	AC3000V, 1分間(感応電流0.5mA) 1次 ⇄ 2次間 AC3000V for 1 minute (Sensing current 0.5mA) Primary ⇄ Secondary			
絶縁抵抗 Insulation resistance	R _{is}	≥500MΩ (at DC500V) 1次 ⇄ 2次間 ≥500MΩ (at DC500V) Primary ⇄ Secondary			
動作温度範囲 Ambient Operating temperature	T _A	-40°C~+85°C			
保存温度範囲 Ambient storage temperature	T _s	-40°C~+90°C			
2次側コイル抵抗値 Secondary coil resistance	R _s	at Ta=70°C 80Ω at Ta=85°C 85Ω	at Ta=70°C 120Ω at Ta=85°C 128Ω	at Ta=70°C 25Ω at Ta=85°C 28Ω	at Ta=70°C 95Ω at Ta=85°C 105Ω

※1 オフセット電流はコアヒステリシス除去後の値とする。 Offset current value is after removal of core hysteresis. ※2: Vcc=±15V, Ta=70°C Ifmax=70AT (at 50Ω≤RL≤90Ω)

※ UL承認条件につきましては、別紙を参照願います。 Please refer to the another sheet about conditions of UL Recognition.

外形図 DIMENSIONS (mm)

